



TablLift™

ECO A CDL Series Scissor Lift Tables



Compact Double,
Electrohydraulic
500 to 2,000 lb.
Capacity
For Surface or
Pit Installation

CDL -15-36-18036

Model Number Format

CDL-15-36-18036

Series "CDL" _____
Compact Lift Table _____
Capacity _____
15 = 1,500 lbs.
Vertical Travel _____
36 = 36 inches
Platform Size _____
18036 = 18"W x 36"L

Description

ECO A CDL Series Compact Double Scissor Lifts are high-speed electrohydraulic scissor lifts with capacities of 500 to 2,000 lbs., travel distance to 36 in. with platform size of 18 x 36 to 30 x 60 in.

All ECO A Lift Tables are designed and constructed for heavy-duty applications under the toughest working conditions, offering years of trouble-free operation.

Standard Features

- Internally-mounted ¾HP, 115V, 1PH, 60Hz intermittent duty TENV super torque motor
- 115V operating control voltage
- NEMA-4X constant-pressure (water-tight, dust-tight and corrosion-resistant) "UP-DOWN" pushbutton box with 8 ft. straight cord
- 10 ft. power cord (connector plug not included)
- Hard, chrome-plated, polished shafting, hydraulic cylinder piston rods and axles
- Surfaces degreased, oxide primed and finished with two coats of enamel
- Smooth steel tops and straight safety toeguards

- Lifetime self-lubricating, anti-friction bearings at all pivot points
- Internal high-pressure gear pump with check valve, relief valve, pressure-compensated flow control valve, solenoid valve, suction and return filters
- Includes hydraulic oil

Limited Warranty Policy

Refer to Warranty Form for specific details. Specifications are subject to change without notice. CDL Series Scissor Lifts are one of a group of ECO A Lift Tables and other materials handling products.

Selector Table for CDL Series. Capacities 500 to 2,000 lbs.

| Travel | Model | Capacity (pounds) | Edge Load* Maximum Static | Platform Sizes (inches) | | Base Frame (inches) | Height (Inches) | | Up Speeds (seconds) | Motor Std. HP | Cylinders (qty.) | Ship* Weight (pounds) |
|--------|-----------|-------------------|---------------------------|-------------------------|---------|---------------------|-----------------|--------|---------------------|---------------|------------------|-----------------------|
| | | | | Standard | Maximum | | Lowered | Raised | | | | |
| 36" | CDL-05-36 | 500 | 250 | 18 x 36 | 30 x 60 | 18 x 36 | 7 | 43 | 13 | ¾ | 1 | 250 |
| | CDL-10-36 | 1,000 | 500 | 18 x 36 | 30 x 60 | 18 x 36 | 7 | 43 | 26 | ¾ | 2 | 295 |
| | CDL-15-36 | 1,500 | 750 | 18 x 36 | 30 x 60 | 18 x 36 | 7 | 43 | 26 | ¾ | 2 | 320 |
| | CDL-20-36 | 2,000 | 1,000 | 18 x 36 | 30 x 60 | 18 x 36 | 7 | 43 | 19 | ¾ | 3 | 340 |

*Standard platforms only. Oversized platforms, beveled toeguards, roller shades, accordion skirting and electrical tape switches will affect overall size. Power requirements depend upon frequency and type of operation and require specific selection. See page 21 for options and accessories.